Date of revision: 15. Oct. 2014. Replace: 23. Jun. 2011

TECHNICAL DATA SHEET

en

Name of product:

FAXE H. S. Micro Oil

Type of product: High Solid oil for floors based on sunflower oil and ennobled wax.

Oil treatment of wooden floors. Can be used for all wood types. Application:

Gives the wood a water and dirt repellent surface. It also retains its natural appearance **Properties:**

and color.

Solids: 95 weight % 94 vol. %

Pre-treatment: The wood has to be sanded, clean and dry. If needed a treatment with Faxe Industrial

Lye can be done. Industrial Lye stops the yellowing of the wood.

Application:

Method: Recommended viscosity: Thinner: White spirit Industrial roller coater 30-40 sec. DIN-cup 4 mm

Drying:

Drying time Film thickness - dry

Dry to touch 1 hour 20 °C 12-15 g / m² Forced dry 20 minutes 50 °C 12-15 g / m² Chemical resistant after 7 day(s) 20 °C 12-15 g / m²

System Specification:

If needed 1x Faxe Industrial Lye

If needed 1x sanding

1x Faxe High Solid Micro Oil

Hereafter can treatment with Faxe Industrial Oilcare be done.

Coverage: Theoretical: 64 m²/ltr.

Frostfree, cool, and closed. Storage: Shelf-life: 24 Months in an unopened container

Cleaning: Application machines can be cleaned with Faxe Machinecleaner.

Product marking: 2004/42/IIA(X)(YY)ZZZ EU directive number: 2004/42/ **VOC** explanation:

> Directive annex number: IIA Product subcategory: (X)

VOC content limit value g/l 2010: (YY)

Maximum VOC Content in this product when ready for use, g/l: ZZZ Please see the can label for information regarding VOC content.

Faxe High Solid Micro Oil gives some repellent effect to stains from eg. coffee an red Note:

wine.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

Esbjerg Farve- & Lakfabrik A/S **Energivej 13** DK- 6700 Esbjerg

Ph. +45 75 12 86 00 FAX +45 75 45 33 68 e-mail: info@esbjergpaints.dk